

# New GMM Estimators for Dynamic Panel Data Models

Ahmed H. Youssef<sup>1</sup>, Ahmed A. El-sheikh<sup>2</sup>, Mohamed R. Abonazel<sup>3</sup>

Professor, Department of Statistics, Faculty of Science, King Abdulaziz University, Jeddah, Kingdom of Saudi Arabia<sup>1</sup>

Associate Professor, Department of Applied Statistics and Econometrics, Institute of Statistical Studies and Research, Cairo University, Cairo, Egypt<sup>2</sup>

Lecturer, Department of Applied Statistics and Econometrics, Institute of Statistical Studies and Research, Cairo University, Cairo, Egypt<sup>3</sup>

**ABSTRACT:** In dynamic panel data (DPD) models, the generalized method of moments (GMM) estimation gives efficient estimators. However, this efficiency is affected by the choice of the initial weighting matrix. In practice, the inverse of the moment matrix of the instruments has been used as an initial weighting matrix which led to a loss of efficiency. Therefore, we will present new GMM estimators based on optimal or suboptimal weighting matrices in GMM estimation. Monte Carlo study indicates that the potential efficiency gain by using these matrices. Moreover, the bias and efficiency of the new GMM estimators are more reliable than any other conventional GMM estimators.

**KEYWORDS:** Dynamic panel data, Generalized method of moments, Monte Carlo simulation, Optimal and suboptimal weighting matrices.

## I. INTRODUCTION

The econometrics literatures focus on three types of GMM estimators when studying the DPD models. The First is first-difference GMM (DIF) estimator which presented by Arellano and Bond [4], and the second is level GMM (LEV) estimator which presented by Arellano and Bover [5], while the third is system GMM (SYS) estimator which presented by Blundell and Bond [6]. Since the SYS estimator combines moment conditions of DIF and LEV estimators, and it is generally known that using many instruments can improve the efficiency of various GMM estimators (Arellano and Bover [5]; Ahn and Schmidt [2]; Blundell and Bond [6]). Therefore, the SYS estimator is more efficient than DIF and LEV estimators. Despite the substantial efficiency gain, using many instruments has two important drawbacks: increased bias and unreliable inference (Newey and Smith [10]; Hayakawa [8]). Moreover, the SYS estimator does not always work well; Bun and Kiviet [7] showed that the bias of SYS estimator becomes large when the autoregressive parameter is close to unity and/or when the ratio of the variance of the individual effect to that of the error term departs from unity.

In general, an asymptotically efficient estimator can be obtained through the two-step procedure in the standard GMM estimation. In the first step, an initial positive semidefinite weighting matrix is used to obtain consistent estimates of the parameters. Given these consistent estimates, a weighting matrix can be constructed and used for asymptotically efficient two-step estimates. Arellano and Bond [4] showed that the two-step estimated standard errors have a small sample downward bias in DPD setting, and one-step estimates with robust standard errors are often preferred. Although an efficient weighting matrix for DIF estimator under the assumption that the errors are homoskedastic and are not serially correlated is easily derived, this is not the case for the LEV and SYS estimators.

In this paper, we will present new LEV and SYS estimators based on optimal or suboptimal weighting matrices, without increase of the moment conditions of these estimators. The new GMM estimators are more efficiency than the conventional GMM estimators.

# International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

This paper is organized as follows. Section II provides the model and reviews the conventional DIF, LEV, and SYS estimators. Section III presents the new GMM estimators. While section IV contains the Monte Carlo simulation study. Finally, section V offers the concluding remarks.

## II. RELATED WORK

Consider a simple DPD process of the form

$$y_{it} = \phi y_{i,t-1} + \mu_i + \varepsilon_{it}, \quad i = 1, \dots, N; \quad t = 1, \dots, T. \tag{1}$$

Under the following assumptions:

- (i)  $\varepsilon_{it}$  are i.i.d across time and individuals and independent of  $\mu_i$  and  $y_{i1}$  with  $E(\varepsilon_{it}) = 0, Var(\varepsilon_{it}) = \sigma_\varepsilon^2$ .
  - (ii)  $\mu_i$  are i.i.d across individuals with  $E(\mu_i) = 0, Var(\mu_i) = \sigma_\mu^2$ .
  - (iii) The initial observations satisfy  $y_{i1} = \frac{\mu_i}{1-\phi} + w_{i1}$  for  $i = 1, \dots, N$ , where  $w_{i1} = \sum_{j=0}^{\infty} \phi^j \varepsilon_{i,1-j}$  and independent of  $\mu_i$ .
- Assumptions (i) and (ii) are the same as in Blundell and Bond [6], while assumption (iii) has been developed by Alvarez and Arellano [3].

Stacking equation (1) over time, we obtain

$$y_i = \phi y_{i,-1} + u_i, \tag{2}$$

where  $y_i = (y_{i3}, \dots, y_{iT})'$ ,  $y_{i,-1} = (y_{i2}, \dots, y_{i,T-1})'$ ,  $u_i = (u_{i3}, \dots, u_{iT})'$ , with  $u_{it} = \mu_i + \varepsilon_{it}$ .

Given these assumptions, we get three types of GMM estimators. These include DIF, LEV, and SYS estimators. In general, the GMM procedure used the suggested weighting matrix to get the one-step estimation, and then used the residuals from one-step estimation as a weighting matrix to get the two-step estimation.

In model (2), the individual effect ( $\mu_i$ ) caused a severe correlation between the lagged endogenous variable ( $y_{i,-1}$ ) and the error term ( $u_i$ ). So, to eliminate this effect, Arellano and Bond [4] have used the first differences as:

$$\Delta y_i = \phi \Delta y_{i,-1} + \Delta u_i, \tag{3}$$

where  $\Delta y_i = (y_{i3} - y_{i2}, \dots, y_{iT} - y_{i,T-1})'$ ,  $\Delta y_{i,-1} = (y_{i2} - y_{i1}, \dots, y_{i,T-1} - y_{i,T-2})'$ , and  $\Delta u_i = (u_{i3} - u_{i2}, \dots, u_{iT} - u_{i,T-1})'$ , and then they showed that

$$E(H_i^{D'} \Delta u_i) = 0, \tag{4}$$

where

$$H_i^D = \begin{pmatrix} y_{i1} & 0 & 0 & \dots & 0 & \dots & 0 \\ 0 & y_{i1} & y_{i2} & \dots & 0 & \dots & 0 \\ \vdots & \vdots & \vdots & \dots & \vdots & \dots & \vdots \\ 0 & 0 & 0 & \dots & y_{i1} & \dots & y_{i,T-2} \end{pmatrix}. \tag{5}$$

Using (4) as the orthogonal conditions in the GMM, Arellano and Bond [4] constructed the one-step first-difference GMM (DIF1) estimator for  $\phi$ , which is given by

$$\hat{\phi}^D = (\Delta y_{-1}' H^D W^D H^{D'} \Delta y_{-1})^{-1} \Delta y_{-1}' H^D W^D H^{D'} \Delta y, \tag{6}$$

where  $\Delta y_{-1} = (\Delta y'_{1,-1}, \dots, \Delta y'_{1,-N})'$ ,  $\Delta y = (\Delta y'_1, \dots, \Delta y'_N)'$ ,  $H^D = (H_1^D, \dots, H_N^D)'$ , and

$$W^D = \left( \frac{1}{N} \sum_{i=1}^N H_i^{D'} D H_i^D \right)^{-1}, \tag{7}$$

## International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

where  $D = FF'$ , and  $F$  is a  $(T - 2) \times (T - 1)$  first-difference operator matrix

$$F = \begin{pmatrix} -1 & 1 & 0 & \dots & 0 \\ 0 & -1 & 1 & \ddots & \vdots \\ \vdots & \ddots & \ddots & \ddots & 0 \\ 0 & \dots & 0 & -1 & 1 \end{pmatrix} \tag{8}$$

To get the two-step first-difference GMM (DIF2) estimator, the moment conditions are weighted by

$$W_{(2)}^D = \left( \frac{1}{N} \sum_{i=1}^N H_i^{D'} \Delta \hat{u}_i \Delta \hat{u}_i' H_i^D \right)^{-1}, \tag{9}$$

where  $\Delta \hat{u}_i$  are the fitted residuals from DIF1 estimator.

Blundell and Bond [6] showed that when  $\phi$  is close to unity and/or  $\sigma_\mu^2 / \sigma_\varepsilon^2$  increases the instruments matrix (5) becomes invalid. This means that the first-difference GMM estimator has weak instruments problem.

Arellano and Bover [5] suggested a new method to eliminate the individual effect from instrumental variables. They considered the level model (2) and then showed that the instrumental variables matrix

$$H_i^L = \begin{pmatrix} \Delta y_{i2} & 0 & \dots & 0 \\ 0 & \Delta y_{i3} & & \vdots \\ \vdots & & \ddots & 0 \\ 0 & \dots & 0 & \Delta y_{i,T-1} \end{pmatrix}, \tag{10}$$

which is not contains individual effect and satisfied the orthogonal conditions

$$E(H_i^{L'} u_i) = 0. \tag{11}$$

Using (11), Arellano and Bover's [5] one-step level GMM (LEV1) estimator is calculated as:

$$\hat{\phi}^L = (y_{-1}' H^L W^L H^L y_{-1})^{-1} y_{-1}' H^L W^L H^L y, \tag{12}$$

where  $y_{-1} = (y'_{1,-1}, \dots, y'_{1,-N})'$ ,  $y = (y'_1, \dots, y'_N)'$ ,  $H^L = (H^L_1, \dots, H^L_N)'$ , and

$$W^L = \left( \frac{1}{N} \sum_{i=1}^N H_i^{L'} H_i^L \right)^{-1}. \tag{13}$$

To get the two-step level GMM (LEV2) estimator, similarly as in DIF2 estimator, the moment conditions are weighted by

$$W_{(2)}^L = \left( \frac{1}{N} \sum_{i=1}^N H_i^{L'} \hat{u}_i \hat{u}_i' H_i^L \right)^{-1}, \tag{14}$$

where  $\hat{u}_i$  are the fitted residuals from LEV1 estimator.

Blundell and Bond [6] proposed a system GMM estimator in which the moment conditions of the first-difference GMM and level GMM are used jointly to avoid weak instruments and improved the efficiency of the estimator. The moment conditions used in constructing the system GMM estimator are given by

$$E(H_i^{S'} u_i^S) = 0, \tag{15}$$

where  $u_i^S = (\Delta u_i', u_i')'$  and  $H_i^S$  is a  $2(T - 2) \times (T - 2) (T + 1) / 2$  block diagonal matrix given by

# International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

$$H_i^S = \begin{pmatrix} H_i^D & 0 \\ 0 & H_i^L \end{pmatrix}. \tag{16}$$

Using (15), the one-step system GMM (SYS1) estimator is calculated as:

$$\hat{\phi}^S = (y_{-1}^{S'} H^S W_G^S H^S y_{-1}^S)^{-1} y_{-1}^{S'} H^S W_G^S H^S y^S, \tag{17}$$

where  $y_{-1}^S = [(\Delta y'_{1,-1}, y'_{1,-1}), \dots, (\Delta y'_{N,-1}, y'_{N,-1})]'$ ,  $y^S = [(\Delta y'_1, y'_1), \dots, (\Delta y'_N, y'_N)]'$ ,  $H^S = (H_1^S, \dots, H_N^S)'$ , and

$$W_G^S = \left( \frac{1}{N} \sum_{i=1}^N H_i^{S'} G H_i^S \right)^{-1}, \tag{18}$$

where

$$G = \begin{pmatrix} D & 0 \\ 0 & I_{T-2} \end{pmatrix}. \tag{19}$$

To get the two-step system GMM (SYS2) estimator, the moment conditions are weighted by

$$W_{G(2)}^S = \left( \frac{1}{N} \sum_{i=1}^N H_i^{S'} \hat{u}_i^S \hat{u}_i^{S'} H_i^S \right)^{-1}, \tag{20}$$

where  $\hat{u}_i^S$  are the fitted residuals from SYS1 estimator.

### III. NEW LEV AND SYS GMM ESTIMATORS

In this section, we present the new GMM estimators, depending on the optimal weighting matrix for LEV estimator, and suboptimal weighting matrices for SYS estimator, through the use of these matrices as new weighting matrices in GMM estimation, and then we get new GMM estimators. The new GMM estimators are more efficiency than the conventional GMM (LEV and SYS) estimators.

In level GMM estimation, Youssefetal.[12] showed that  $W^L$  is an optimal weighting matrix only in the case of  $\sigma_\mu^2 = 0$ , i.e. no individual effects case, and they presented an optimal weighting matrix for LEV estimator, in general case, as:

$$W^{OL} = \left( \frac{1}{N} \sum_{i=1}^N H_i^{L'} J_{T-2} H_i^L \right)^{-1}, \tag{21}$$

where

$$J_{T-2} = \begin{pmatrix} 1 + \rho & \rho & \rho & \dots & \rho \\ \rho & 1 + \rho & \rho & \dots & \rho \\ \rho & \rho & 1 + \rho & \dots & \rho \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ \rho & \rho & \rho & \dots & 1 + \rho \end{pmatrix}; \rho = \sigma_\mu^2 / \sigma_\varepsilon^2. \tag{22}$$

Note that the use of the weighting matrix  $W^{OL}$  can be described as inducing cross-sectional heterogeneity through  $\rho$ , and also can be explained as partially adopting a procedure of generalized least squares to the level estimation. So using  $W^{OL}$ , instead of  $W^L$ , certainly improve the efficiency of level GMM estimator. So, we will present an alternative LEV estimator depending on the optimal weighting matrix,  $W^{OL}$ , as given in (21). The optimal one-step weighted LEV (WLEV1) estimator is given by

$$\hat{\phi}^{WL} = (y_{-1}' H^L W^{OL} H^L y_{-1})^{-1} y_{-1}' H^L W^{OL} H^L y. \tag{23}$$

**Table 1:** Bias and RMSE for conventional and weighted level GMM estimators when  $N = 50$

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$		
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$

## International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

$\rho = 0$										
Bias	LEV1	-0.0007	0.0005	0.0026	0.0008	0.0022	0.0008	-0.0081	-0.0054	-0.0004
	LEV2	0.0049	0.0083	0.0096	0.0039	0.0068	0.0047	-0.0084	-0.0035	0.0006
	WLEV1	-0.0010	0.0005	0.0025	0.0006	0.0021	0.0007	-0.0087	-0.0064	-0.0013
	WLEV2	0.0032	0.0070	0.0086	0.0018	0.0041	0.0023	-0.0138	-0.0184	-0.0171
RMSE	LEV1	0.1186	0.0759	0.0622	0.1367	0.0841	0.0656	0.1006	0.0694	0.0584
	LEV2	0.1230	0.0830	0.0678	0.1428	0.0910	0.0720	0.1043	0.0736	0.0633
	WLEV1	0.1189	0.0760	0.0622	0.1369	0.0841	0.0656	0.1010	0.0699	0.0587
	WLEV2	0.1240	0.0833	0.0678	0.1450	0.0911	0.0722	0.1084	0.0833	0.0717
$\rho = 0.5$										
Bias	LEV1	0.0339	0.0276	0.0291	0.0346	0.0421	0.0482	0.0445	0.0598	0.0640
	LEV2	0.0298	0.0269	0.0294	0.0295	0.0379	0.0427	0.0421	0.0582	0.0637
	WLEV1	0.0255	0.0167	0.0177	0.0246	0.0269	0.0307	0.0414	0.0549	0.0584
	WLEV2	0.0110	-0.0028	0.0008	0.0068	-0.0056	-0.0043	0.0377	0.0409	0.0339
RMSE	LEV1	0.1404	0.0835	0.0673	0.1530	0.0974	0.0826	0.1158	0.0761	0.0733
	LEV2	0.1473	0.0887	0.0715	0.1608	0.1030	0.0859	0.1237	0.0781	0.0754
	WLEV1	0.1403	0.0806	0.0620	0.1556	0.0927	0.0741	0.1224	0.0760	0.0706
	WLEV2	0.1455	0.0823	0.0613	0.1631	0.0940	0.0726	0.1263	0.0780	0.0686
$\rho = 1$										
Bias	LEV1	0.0572	0.0538	0.0585	0.0824	0.0885	0.0696	0.0754	0.0789	0.0572
	LEV2	0.0463	0.0432	0.0415	0.0644	0.0718	0.0690	0.0744	0.0782	0.0463
	WLEV1	0.0316	0.0259	0.0388	0.0489	0.0488	0.0679	0.0722	0.0752	0.0316
	WLEV2	0.0033	-0.0008	0.0140	-0.0006	-0.0025	0.0659	0.0634	0.0587	0.0033
RMSE	LEV1	0.1029	0.0852	0.1760	0.1243	0.1139	0.1193	0.0844	0.0842	0.1029
	LEV2	0.1032	0.0831	0.1853	0.1197	0.1063	0.1231	0.0851	0.0843	0.1032
	WLEV1	0.0895	0.0688	0.1793	0.1061	0.0872	0.1203	0.0836	0.0822	0.0895
	WLEV2	0.0858	0.0667	0.1848	0.0968	0.0742	0.1241	0.0822	0.0761	0.0858
$\rho = 25$										
Bias	LEV1	0.4281	0.4798	0.4933	0.3976	0.4090	0.4136	0.0985	0.0985	0.0986
	LEV2	0.3240	0.3589	0.3879	0.3746	0.3791	0.3899	0.0985	0.0987	0.0985
	WLEV1	0.2914	0.2075	0.1623	0.3701	0.3378	0.3093	0.0984	0.0984	0.0985
	WLEV2	0.2381	0.0781	0.0294	0.3527	0.2340	0.1197	0.0982	0.0982	0.0974
RMSE	LEV1	0.5754	0.4966	0.5036	0.4312	0.4140	0.4162	0.1006	0.0990	0.0988
	LEV2	0.5799	0.3990	0.4135	0.4321	0.3909	0.3958	0.1010	0.0992	0.0988
	WLEV1	0.5677	0.2553	0.1941	0.4270	0.3567	0.3231	0.1006	0.0989	0.0988
	WLEV2	0.5365	0.1400	0.0829	0.4223	0.2721	0.1587	0.1009	0.0988	0.0978

To obtain the two-step weighted LEV (WLEV2) estimator, we will suggest the following weighting to the moment conditions:

$$W_{(2)}^{OL} = \left( \frac{1}{N} \sum_{i=1}^N H_i^{L'} J_{T-2} \hat{u}_i \hat{u}_i' J_{T-2} H_i^L \right)^{-1}, \tag{24}$$

where  $\hat{u}_i$  are residuals from WLEV1 estimator. Note that, we use  $J_{T-2}$  in (24) to improve the efficiency of WLEV2, as will be shown in our simulation results below.

**Table 2:** Bias and RMSE for conventional and weighted level GMM estimators when  $N = 100$

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$			
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	
$\rho = 0$										
Bias	LEV1	0.0040	-0.0007	0.0015	0.0003	-0.0005	0.0001	-0.0097	-0.0019	-0.0020
	LEV2	0.0059	0.0037	0.0060	0.0010	0.0020	0.0035	-0.0091	-0.0005	-0.0009

## International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

	WLEV1	0.0040	-0.0007	0.0015	0.0002	-0.0005	0.0000	-0.0098	-0.0021	-0.0023
	WLEV2	0.0056	0.0035	0.0058	0.0001	0.0011	0.0026	-0.0111	-0.0050	-0.0069
RMSE	LEV1	0.0915	0.0560	0.0431	0.0982	0.0623	0.0462	0.0781	0.0490	0.0424
	LEV2	0.0939	0.0594	0.0466	0.1006	0.0651	0.0491	0.0790	0.0509	0.0443
	WLEV1	0.0916	0.0560	0.0431	0.0984	0.0623	0.0462	0.0782	0.0491	0.0425
	WLEV2	0.0944	0.0594	0.0465	0.1014	0.0655	0.0491	0.0806	0.0532	0.0468
<b><math>\rho = 0.5</math></b>										
Bias	LEV1	0.0090	0.0165	0.0161	0.0201	0.0273	0.0260	0.0288	0.0455	0.0518
	LEV2	0.0080	0.0163	0.0155	0.0164	0.0232	0.0218	0.0259	0.0426	0.0489
	WLEV1	0.0049	0.0108	0.0102	0.0148	0.0186	0.0167	0.0258	0.0415	0.0460
	WLEV2	-0.0022	0.0004	0.0005	0.0048	-0.0001	-0.0019	0.0223	0.0305	0.0261
RMSE	LEV1	0.0973	0.0566	0.0473	0.1131	0.0676	0.0543	0.0879	0.0609	0.0606
	LEV2	0.0995	0.0585	0.0495	0.1148	0.0693	0.0548	0.0914	0.0610	0.0603
	WLEV1	0.0970	0.0553	0.0455	0.1136	0.0653	0.0506	0.0909	0.0604	0.0576
	WLEV2	0.0989	0.0561	0.0457	0.1147	0.0650	0.0497	0.0926	0.0592	0.0530
<b><math>\rho = 1</math></b>										
Bias	LEV1	0.0255	0.0271	0.0257	0.0372	0.0474	0.0503	0.0482	0.0630	0.0663
	LEV2	0.0180	0.0196	0.0199	0.0271	0.0334	0.0350	0.0452	0.0595	0.0642
	WLEV1	0.0152	0.0137	0.0115	0.0252	0.0270	0.0272	0.0454	0.0591	0.0613
	WLEV2	0.0038	-0.0005	-0.0012	0.0109	0.0007	-0.0003	0.0428	0.0505	0.0452
RMSE	LEV1	0.1081	0.0656	0.0530	0.1220	0.0827	0.0728	0.1299	0.0723	0.0714
	LEV2	0.1094	0.0634	0.0523	0.1245	0.0793	0.0658	0.1388	0.0712	0.0704
	WLEV1	0.1070	0.0600	0.0472	0.1216	0.0736	0.0588	0.1401	0.0712	0.0682
	WLEV2	0.1074	0.0587	0.0475	0.1231	0.0692	0.0522	0.1388	0.0682	0.0600
<b><math>\rho = 25</math></b>										
Bias	LEV1	0.3035	0.3520	0.3661	0.3476	0.3508	0.3585	0.0978	0.0978	0.0981
	LEV2	0.1770	0.1826	0.1961	0.3138	0.2867	0.2933	0.0977	0.0975	0.0978
	WLEV1	0.1485	0.0974	0.0717	0.3054	0.2343	0.1965	0.0976	0.0976	0.0979
	WLEV2	0.1115	0.0473	0.0195	0.2929	0.1513	0.0848	0.0975	0.0971	0.0968
RMSE	LEV1	0.3819	0.3719	0.3798	0.4223	0.3588	0.3626	0.1007	0.0982	0.0983
	LEV2	0.3418	0.2266	0.2283	0.4329	0.3088	0.3067	0.1010	0.0980	0.0981
	WLEV1	0.3122	0.1409	0.0994	0.4218	0.2608	0.2151	0.1009	0.0981	0.0981
	WLEV2	0.2917	0.1042	0.0614	0.4211	0.1831	0.1092	0.1009	0.0977	0.0972

**Table 3:** Bias and RMSE for conventional and weighted system GMM estimators when  $N= 50$  and  $\rho = 0, 0.5$

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$			
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	
<b><math>\rho = 0</math></b>										
Bias	SYS1	-0.0139	-0.0164	-0.0145	-0.0227	-0.0227	-0.0235	-0.0332	-0.0541	-0.0558
	SYS2	-0.0068	-0.0159	-0.0199	-0.0170	-0.0208	-0.0373	-0.0127	-0.0503	-0.0695
	WCSYS1	-0.0086	-0.0050	-0.0010	-0.0172	-0.0056	-0.0032	-0.0107	-0.0082	-0.0040
	WCSYS2	-0.0028	-0.0052	-0.0115	-0.0117	-0.0048	-0.0262	-0.0016	-0.0071	-0.0401
	WCJSYS1	-0.0129	-0.0074	-0.0036	-0.0238	-0.0103	-0.0083	-0.0172	-0.0180	-0.0173
	WCJSYS2	-0.0043	-0.0075	-0.0130	-0.0143	-0.0092	-0.0290	-0.0047	-0.0163	-0.0473
	WJSYS1	-0.0144	-0.0165	-0.0146	-0.0239	-0.0229	-0.0236	-0.0369	-0.0573	-0.0580
	WJSYS2	-0.0070	-0.0159	-0.0199	-0.0175	-0.0210	-0.0374	-0.0146	-0.0533	-0.0709

**International Journal of Innovative Research in Science,  
Engineering and Technology**

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

RMSE	SYS1	0.0989	0.0603	0.0476	0.1204	0.0669	0.0514	0.1095	0.0852	0.0732
	SYS2	0.1041	0.0611	0.0591	0.1193	0.0664	0.0677	0.0929	0.0819	0.0905
	WCSYS1	0.0905	0.0529	0.0405	0.1045	0.0528	0.0391	0.0744	0.0368	0.0248
	WCSYS2	0.1038	0.0548	0.0536	0.1166	0.0542	0.0586	0.0834	0.0379	0.0627
	WCJSYS1	0.0924	0.0538	0.0415	0.1078	0.0551	0.0412	0.0804	0.0431	0.0328
	WCJSYS2	0.1045	0.0557	0.0545	0.1181	0.0562	0.0606	0.0863	0.0434	0.0687
	WJSYS1	0.0993	0.0603	0.0476	0.1211	0.0671	0.0515	0.1143	0.0887	0.0754
	WJSYS2	0.1042	0.0611	0.0591	0.1196	0.0665	0.0678	0.0954	0.0851	0.0918
$\rho = 0.5$										
Bias	SYS1	0.0103	-0.0062	-0.0052	0.0042	-0.0090	-0.0104	0.0233	0.0268	0.0196
	SYS2	0.0179	-0.0058	-0.0145	0.0117	-0.0077	-0.0294	0.0115	0.0266	-0.0041
	WCSYS1	0.0365	0.0655	0.0965	0.0360	0.0795	0.1122	0.0410	0.0632	0.0695
	WCSYS2	0.0318	0.0616	0.0460	0.0317	0.0760	0.0411	0.0290	0.0623	0.0319
	WCJSYS1	0.0103	0.0046	0.0069	0.0025	0.0076	0.0060	0.0128	0.0399	0.0417
	WCJSYS2	0.0197	0.0044	-0.0073	0.0137	0.0080	-0.0197	0.0076	0.0394	0.0124
	WJSYS1	0.0019	-0.0124	-0.0106	-0.0116	-0.0205	-0.0202	0.0017	0.0113	0.0040
	WJSYS2	0.0143	-0.0116	-0.0178	0.0036	-0.0185	-0.0353	-0.0049	0.0112	-0.0160
RMSE	SYS1	0.1198	0.0639	0.0467	0.1377	0.0723	0.0506	0.1043	0.0574	0.0418
	SYS2	0.1205	0.0645	0.0592	0.1342	0.0724	0.0678	0.1112	0.0572	0.0510
	WCSYS1	0.1170	0.0928	0.1116	0.1292	0.1039	0.1243	0.0893	0.0683	0.0714
	WCSYS2	0.1228	0.0902	0.0764	0.1369	0.1018	0.0749	0.1075	0.0681	0.0520
	WCJSYS1	0.1122	0.0602	0.0453	0.1299	0.0694	0.0480	0.1266	0.0665	0.0555
	WCJSYS2	0.1208	0.0614	0.0569	0.1379	0.0705	0.0629	0.1309	0.0666	0.0527
	WJSYS1	0.1214	0.0654	0.0475	0.1449	0.0765	0.0543	0.1348	0.0713	0.0488
	WJSYS2	0.1206	0.0659	0.0601	0.1370	0.0761	0.0707	0.1335	0.0710	0.0600

In system GMM estimation, Windmeijer[11] showed that the optimal weighting matrix for SYS estimator has only been obtained in case of  $\sigma_\mu^2 = 0$ , and this matrix is given by:

$$W_c^S = \left( \frac{1}{N} \sum_{i=1}^N H_i^{S'} G_c H_i^S \right)^{-1}, \tag{25}$$

where

$$G_c = \begin{pmatrix} D & C \\ C' & I_{T-2} \end{pmatrix}, \tag{26}$$

and  $C$  is a  $(T - 2)$  square matrix:

$$C = \begin{pmatrix} 1 & 0 & 0 & \dots & 0 \\ -1 & 1 & 0 & \ddots & \vdots \\ 0 & -1 & 1 & \ddots & 0 \\ \vdots & \ddots & \ddots & \ddots & 0 \\ 0 & \dots & 0 & -1 & 1 \end{pmatrix}. \tag{27}$$

Youssef et al.[12] presented the following suboptimal weighting matrices:

$$W_{cj}^S = \left( \frac{1}{N} \sum_{i=1}^N H_i^{S'} G_{cj} H_i^S \right)^{-1}, \quad \text{with } G_{cj} = \begin{pmatrix} D & C \\ C' & J_{T-2} \end{pmatrix}, \tag{28}$$

$$W_j^S = \left( \frac{1}{N} \sum_{i=1}^N H_i^{S'} G_j H_i^S \right)^{-1}, \quad \text{with } G_j = \begin{pmatrix} D & 0 \\ 0 & J_{T-2} \end{pmatrix}. \tag{29}$$

So, we will present two alternatives for SYS estimators as:

# International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

- (a) One-step and two-step weighted SYS (WCJSYS1 and WCJSYS2) estimators which depending on  $W_{cj}^S$  instead of  $W_G^S$  matrix.
- (b) One-step and two-step weighted SYS (WJSYS1 and WJSYS2) estimators which depending on  $W_j^S$  instead of  $W_G^S$  matrix.

In addition to the above, we will propose other alternatives SYS (WCJSYS1 and WCJSYS2) estimators by using  $W_c^S$ , which given in (25), instead of  $W_G^S$  matrix to study the performance of these estimators, especially when  $\sigma_\mu^2 > 0$ .

In practice, the variance ratio,  $\rho$ , is unknown. So we will use the suggested estimates by Jung and Kwon [9] for  $\sigma_\epsilon^2$  and  $\sigma_\mu^2$ :

$$\hat{\sigma}_\epsilon^2 = \frac{\sum_{i=1}^N \Delta \hat{u}_i' \Delta \hat{u}_i}{2N(T-2)}, \tag{30}$$

where  $\Delta \hat{u}_i$  are the residuals from DIF1 estimator which given in (6). While  $\hat{\sigma}_\mu^2$  is given by

$$\hat{\sigma}_\mu^2 = \frac{\sum_{i=1}^N [\tilde{u}_i' \tilde{u}_i - (\Delta \tilde{u}_i' \Delta \tilde{u}_i / 2)]}{N(T-2)}, \tag{31}$$

where  $\tilde{u}_i$  and  $\Delta \tilde{u}_i$  are residuals from first-difference and level equations in SYS1 estimator, which given in (17), respectively. Abonazel[1] studied the performance of  $\hat{\rho} = \hat{\sigma}_\mu^2 / \hat{\sigma}_\epsilon^2$  and showed that in cases of  $\rho < 5$  the bias of  $\hat{\rho}$ , Bias ( $\hat{\rho}$ ), close to zero, while in the case of increasing  $\rho$  (specifically when  $\rho \geq 5$ ) the Bias ( $\hat{\rho}$ ) increases significantly, especially when  $\phi$  increases and is close to one.

## IV. MONTE CARLO SIMULATION RESULTS

In this section, we illustrate the small and moderate samples performance of different GMM estimation procedures that are considered according to their weighting matrices. Monte Carlo experiments were carried out based on the following data generating process:

$$y_{it} = \phi y_{i,t-1} + \mu_i + \epsilon_{it}, \tag{32}$$

where  $\mu_i \sim N(0, \sigma_\mu^2)$  is independent across  $i$ ,  $\epsilon_{it} \sim N(0,1)$  is independent across  $i$  and  $t$ ,  $\mu_i$  and  $\epsilon_{it}$  such that they are independent of each other. We generate the initial conditions  $y_{i1}$  as

$$y_{i1} = \frac{\mu_i}{1-\phi} + w_{i1}, \tag{33}$$

where  $w_{i1} \sim N(0, \sigma_{w1}^2)$ , independent of both  $\mu_i$  and  $\epsilon_{it}$  with variance  $\sigma_{w1}^2$  that chosen to satisfy covariance stationarity. Since,  $\rho$  is characterized by  $\sigma_\mu^2 / \sigma_\epsilon^2$ , so we choose  $\sigma_\mu^2 = 0, 0.5, 1, \text{ and } 25$ . Throughout the experiments,  $N = 50, 100$ , and nine parameter settings (i.e.,  $\phi = 0.2, 0.5, 0.9$  and  $T = 5, 10, 15$ ) are simulated. For all experiments we ran 1000 replications and all the results for all separate experiments are obtained by precisely the same series of random numbers.

To compare the small and moderate samples performance, the six different GMM estimation procedures are considered according to their weighting matrix. Specifically, LEV1(2), WLEV1(2), SYS1(2), WCSYS1(2), WCJSYS1(2), and WJSYS1(2). Moreover, we calculate the bias and root mean squared error (RMSE) for each GMM estimator. The bias and RMSE for a Monte Carlo experiment are calculated by

$$\text{Bias} = \frac{1}{1000} \sum_{l=1}^{1000} (\hat{\phi} - \phi); \text{ RMSE} = \sqrt{\frac{1}{1000} \sum_{l=1}^{1000} (\hat{\phi} - \phi)^2}, \tag{34}$$

where  $\phi$  is the true value for  $y_{i,t-1}$  parameter in (32), and  $\hat{\phi}$  is the estimated value for  $\phi$ .

**Table 4:** Bias and RMSE for conventional and weighted system GMM estimators when  $N= 50$  and  $\rho = 1, 25$

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$		
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$



## International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

$\rho = 1$										
Bias	SYS1	0.0107	0.0056	0.0288	0.0168	0.0111	0.0544	0.0531	0.0466	0.0107
	SYS2	0.0108	-0.0074	0.0247	0.0174	-0.0124	0.0455	0.0522	0.0263	0.0108
	WCSYS1	0.1197	0.1669	0.0652	0.1383	0.1862	0.0650	0.0774	0.0817	0.1197
	WCSYS2	0.1136	0.0923	0.0497	0.1335	0.0934	0.0561	0.0762	0.0533	0.1136
	WCJSYS1	0.0113	0.0078	0.0146	0.0201	0.0158	0.0446	0.0643	0.0636	0.0113
	WCJSYS2	0.0115	-0.0061	0.0199	0.0205	-0.0094	0.0380	0.0633	0.0396	0.0115
	WJSYS1	-0.0045	-0.0081	0.0012	-0.0099	-0.0127	0.0360	0.0421	0.0345	-0.0045
	WJSYS2	-0.0034	-0.0160	0.0095	-0.0082	-0.0278	0.0298	0.0413	0.0168	-0.0034
RMSE	SYS1	0.0694	0.0509	0.1473	0.0784	0.0529	0.1007	0.0666	0.0557	0.0694
	SYS2	0.0695	0.0587	0.1424	0.0784	0.0645	0.1130	0.0662	0.0527	0.0695
	WCSYS1	0.1456	0.1813	0.1452	0.1580	0.1954	0.0959	0.0802	0.0827	0.1456
	WCSYS2	0.1404	0.1157	0.1467	0.1544	0.1150	0.1103	0.0795	0.0638	0.1404
	WCJSYS1	0.0665	0.0491	0.1404	0.0810	0.0556	0.1121	0.0875	0.0702	0.0665
	WCJSYS2	0.0671	0.0573	0.1466	0.0815	0.0641	0.1253	0.0871	0.0597	0.0671
	WJSYS1	0.0689	0.0512	0.1556	0.0804	0.0552	0.1153	0.0704	0.0552	0.0689
	WJSYS2	0.0689	0.0602	0.1465	0.0800	0.0702	0.1270	0.0701	0.0560	0.0689
$\rho = 25$										
Bias	SYS1	0.3544	0.3410	0.3207	0.3645	0.3439	0.3251	0.0977	0.0972	0.0965
	SYS2	0.3209	0.3380	0.2642	0.3497	0.3431	0.2816	0.0969	0.0971	0.0941
	WCSYS1	0.5101	0.6288	0.6855	0.4133	0.4516	0.4644	0.0981	0.0987	0.0991
	WCSYS2	0.4660	0.6266	0.5613	0.3911	0.4510	0.3992	0.0973	0.0986	0.0966
	WCJSYS1	0.2334	0.1345	0.0909	0.2496	0.2977	0.2491	0.0941	0.0972	0.0996
	WCJSYS2	0.2205	0.1333	0.0745	0.3186	0.2970	0.2176	0.0938	0.0970	0.0971
	WJSYS1	0.1978	0.0820	0.0499	0.2995	0.2278	0.1720	0.0939	0.0966	0.0962
	WJSYS2	0.1741	0.0813	0.0396	0.2972	0.2272	0.1499	0.0936	0.0965	0.0938
RMSE	SYS1	0.4304	0.3635	0.3360	0.3919	0.3522	0.3305	0.0998	0.0976	0.0967
	SYS2	0.4064	0.3612	0.2849	0.3887	0.3517	0.2913	0.1014	0.0975	0.0948
	WCSYS1	0.5609	0.6355	0.6877	0.4332	0.4534	0.4650	0.0994	0.0988	0.0991
	WCSYS2	0.5349	0.6337	0.5679	0.4215	0.4529	0.4025	0.1011	0.0987	0.0970
	WCJSYS1	0.3936	0.1930	0.1273	3.5190	0.3332	0.2755	0.1023	0.1000	0.1012
	WCJSYS2	0.3727	0.1920	0.1159	0.3972	0.3328	0.2482	0.1026	0.1000	0.0991
	WJSYS1	0.6546	0.1377	0.0862	0.3705	0.2702	0.2021	0.1024	0.0972	0.0965
	WJSYS2	0.3285	0.1369	0.0826	0.3711	0.2699	0.1846	0.1024	0.0971	0.0946

**Table 5: Bias and RMSE for conventional and weighted system GMM estimators when  $N=100$  and  $\rho = 0, 0.5$**

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$			
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	
$\rho = 0$										
Bias	SYS1	-0.0034	-0.0085	-0.0072	-0.0110	-0.0126	-0.0127	-0.0240	-0.0283	-0.0343
	SYS2	-0.0022	-0.0040	-0.0072	-0.0065	-0.0085	-0.0125	-0.0055	-0.0161	-0.0335
	WCSYS1	-0.0025	-0.0013	-0.0011	-0.0072	-0.0039	-0.0014	-0.0065	-0.0020	-0.0033
	WCSYS2	-0.0009	0.0003	-0.0013	-0.0036	-0.0032	-0.0014	-0.0008	0.0000	-0.0031
	WCJSYS1	-0.0049	-0.0024	-0.0019	-0.0109	-0.0058	-0.0033	-0.0088	-0.0052	-0.0079
	WCJSYS2	-0.0014	-0.0003	-0.0020	-0.0045	-0.0043	-0.0033	-0.0014	-0.0019	-0.0076
	WJSYS1	-0.0036	-0.0085	-0.0072	-0.0116	-0.0126	-0.0127	-0.0252	-0.0293	-0.0349
	WJSYS2	-0.0023	-0.0041	-0.0072	-0.0067	-0.0086	-0.0125	-0.0059	-0.0167	-0.0342
RMSE	SYS1	0.0782	0.0437	0.0327	0.0839	0.0480	0.0337	0.0844	0.0560	0.0494
	SYS2	0.0769	0.0448	0.0331	0.0788	0.0473	0.0339	0.0639	0.0424	0.0486
	WCSYS1	0.0712	0.0373	0.0288	0.0709	0.0384	0.0265	0.0547	0.0249	0.0174

## International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

	WCSYS2	0.0765	0.0428	0.0294	0.0778	0.0437	0.0269	0.0589	0.0277	0.0177
	WCJSYS1	0.0716	0.0377	0.0290	0.0721	0.0393	0.0272	0.0571	0.0264	0.0199
	WCJSYS2	0.0766	0.0430	0.0296	0.0781	0.0442	0.0276	0.0597	0.0286	0.0200
	WJSYS1	0.0783	0.0437	0.0327	0.0843	0.0480	0.0337	0.0861	0.0570	0.0502
	WJSYS2	0.0770	0.0448	0.0331	0.0789	0.0474	0.0339	0.0644	0.0430	0.0493
<b><math>\rho = 0.5</math></b>										
Bias	SYS1	-0.0005	-0.0013	-0.0026	0.0037	-0.0018	-0.0050	0.0153	0.0219	0.0157
	SYS2	0.0038	0.0022	-0.0026	0.0044	0.0002	-0.0049	0.0040	0.0171	0.0155
	WCSYS1	0.0121	0.0365	0.0524	0.0160	0.0457	0.0670	0.0271	0.0457	0.0541
	WCSYS2	0.0085	0.0248	0.0513	0.0118	0.0304	0.0658	0.0151	0.0376	0.0536
	WCJSYS1	0.0005	0.0048	0.0035	-0.0001	0.0058	0.0057	0.0065	0.0289	0.0302
	WCJSYS2	0.0050	0.0060	0.0035	0.0052	0.0052	0.0056	0.0018	0.0236	0.0299
	WJSYS1	-0.0043	-0.0044	-0.0053	-0.0048	-0.0080	-0.0099	-0.0014	0.0112	0.0033
	WJSYS2	0.0028	0.0004	-0.0052	0.0017	-0.0035	-0.0096	-0.0066	0.0079	0.0033
RMSE	SYS1	0.0868	0.0457	0.0345	0.1053	0.0513	0.0368	0.0851	0.0481	0.0357
	SYS2	0.0850	0.0464	0.0346	0.0963	0.0480	0.0370	0.0944	0.0463	0.0356
	WCSYS1	0.0844	0.0598	0.0653	0.0988	0.0672	0.0781	0.0740	0.0520	0.0565
	WCSYS2	0.0859	0.0535	0.0644	0.0966	0.0569	0.0770	0.0891	0.0489	0.0561
	WCJSYS1	0.0812	0.0423	0.0318	0.0982	0.0459	0.0340	0.1024	0.0493	0.0428
	WCJSYS2	0.0855	0.0459	0.0322	0.0971	0.0466	0.0343	0.1012	0.0487	0.0426
	WJSYS1	0.0873	0.0462	0.0348	0.1092	0.0528	0.0383	0.1113	0.0549	0.0406
	WJSYS2	0.0849	0.0465	0.0350	0.0970	0.0486	0.0384	0.1071	0.0526	0.0404

The results are given in Tables 1 to 6. Specifically, Tables 1 and 2 present the bias and RMSE of conventional and weighted level GMM estimators for the small,  $N = 50$ , and moderate,  $N = 100$ , samples, respectively. While Tables 3 to 6 present the bias and RMSE of conventional and weighted system GMM estimators, since Tables 3 and 4 dedicated for  $N = 50$ , while Tables 5 and 6 dedicated for  $N = 100$ .

From Tables 1 and 2, We can note that in case of  $\rho = 0$ , the bias and RMSE values for conventional level GMM (LEV1, LEV2) estimators equivalent to the bias and RMSE values for weighted level GMM estimators (WLEV1, WLEV2), the reason that when  $\rho = 0$  lead to  $\hat{f}_{T-2} \cong I_{T-2}$ . Unless  $\rho = 0$ , WLEV2 estimator is smaller in bias and RMSE than other level GMM estimators, which indicates that the use of  $W^{OL}$  as a weighting matrix for level GMM estimator lead to improve the efficiency for this estimator. Moreover, the bias and RMSE for LEV1, LEV2, WLEV1, and WLEV2 estimators in Table 2 are smaller than the bias and MSE in Table 1 because the sample size was increased from 50 to 100.

**Table 6:** Bias and RMSE for conventional and weighted system GMM estimators when  $N = 100$  and  $\rho = 1, 25$

GMM Estimator	$\phi = 0.2$			$\phi = 0.5$			$\phi = 0.9$			
	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	$T = 5$	$T = 10$	$T = 15$	
<b><math>\rho = 1</math></b>										
Bias	SYS1	0.0101	0.0050	0.0012	0.0201	0.0094	0.0060	0.0392	0.0442	0.0382
	SYS2	0.0076	0.0043	0.0014	0.0175	0.0076	0.0059	0.0254	0.0389	0.0380
	WCSYS1	0.0328	0.0666	0.0925	0.0380	0.0861	0.1138	0.0478	0.0640	0.0704
	WCSYS2	0.0154	0.0420	0.0908	0.0282	0.0596	0.1119	0.0338	0.0572	0.0699
	WCJSYS1	0.0063	0.0065	0.0027	0.0107	0.0104	0.0071	0.0276	0.0497	0.0505
	WCJSYS2	0.0070	0.0054	0.0029	0.0153	0.0083	0.0070	0.0206	0.0444	0.0502
	WJSYS1	-0.0003	-0.0026	-0.0055	0.0029	-0.0058	-0.0068	0.0227	0.0331	0.0261
	WJSYS2	0.0046	-0.0003	-0.0052	0.0105	-0.0025	-0.0067	0.0145	0.0287	0.0259
RMSE	SYS1	0.0941	0.0488	0.0354	0.1082	0.0574	0.0401	0.0882	0.0579	0.0472

# International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

	SYS2	0.0886	0.0475	0.0354	0.0996	0.0540	0.0401	0.0934	0.0551	0.0471
	WCSYS1	0.0985	0.0892	0.1048	0.1105	0.1048	0.1235	0.0782	0.0677	0.0717
	WCSYS2	0.0893	0.0674	0.1032	0.1044	0.0824	0.1217	0.0886	0.0637	0.0712
	WCJSYS1	0.0879	0.0460	0.0330	0.1027	0.0552	0.0381	0.1037	0.0665	0.0577
	WCJSYS2	0.0882	0.0465	0.0331	0.1014	0.0536	0.0383	0.1021	0.0635	0.0574
	WJSYS1	0.0949	0.0484	0.0359	0.1123	0.0585	0.0405	0.1104	0.0616	0.0457
	WJSYS2	0.0886	0.0470	0.0358	0.1001	0.0545	0.0405	0.1055	0.0593	0.0456
$\rho = 25$										
Bias	SYS1	0.2554	0.2277	0.2122	0.3041	0.2776	0.2567	0.0970	0.0963	0.0956
	SYS2	0.2126	0.2013	0.2110	0.2838	0.2665	0.2558	0.0952	0.0958	0.0955
	WCSYS1	0.3864	0.5284	0.5992	0.3670	0.4136	0.4353	0.0968	0.0979	0.0985
	WCSYS2	0.3269	0.5007	0.5979	0.3356	0.4050	0.4344	0.0956	0.0974	0.0983
	WCJSYS1	0.1205	0.0422	0.0250	0.2701	0.1749	0.1180	0.0924	0.0630	0.0987
	WCJSYS2	0.1148	0.0369	0.0247	0.2463	0.1682	0.1176	0.0911	0.0794	0.0986
	WJSYS1	0.0934	0.0249	0.0128	0.2170	0.1226	0.0764	0.0924	0.0956	0.0951
	WJSYS2	0.0889	0.0216	0.0126	0.2154	0.1174	0.0761	0.0907	0.0951	0.0950
RMSE	SYS1	0.3209	0.2497	0.2279	0.3426	0.2890	0.2639	0.0998	0.0967	0.0958
	SYS2	0.2919	0.2280	0.2268	0.3359	0.2805	0.2631	0.1007	0.0963	0.0957
	WCSYS1	0.4452	0.5390	0.6040	0.3978	0.4178	0.4366	0.0989	0.0981	0.0986
	WCSYS2	0.4078	0.5164	0.6028	0.3787	0.4108	0.4357	0.1004	0.0977	0.0984
	WCJSYS1	0.3235	0.0858	0.0546	0.5440	0.2191	0.1473	0.0975	1.1273	0.0998
	WCJSYS2	0.2281	0.0800	0.0545	0.3401	0.2146	0.1469	0.0988	0.5963	0.0997
	WJSYS1	0.2005	0.0712	0.0459	0.3051	0.1672	0.1040	0.0983	0.0962	0.0954
	WJSYS2	0.1897	0.0661	0.0459	0.3038	0.1631	0.1037	0.0988	0.0957	0.0953

From Tables 3 to 6, as in results level GMM estimation, we can note that in case of  $\rho = 0$ , the bias and RMSE values for SYS1 and SYS2 equivalent to the bias and RMSE values for WJSYS1 and WJSYS2. Moreover, WCSYS2 estimator is smaller in bias and RMSE (when  $\rho = 0$  only) than other system GMM estimators. But when  $0 < \rho \leq 1$ , we find that SYS2 and WJSYS2 are smaller in bias and RMSE than other system GMM estimators. Moreover, when  $\rho \geq 5$ , WCJSYS2 and WJSYS2 estimators are the smallest in bias and RMSE even in the case of increasing  $\phi$  and is close to one. Moreover, the bias and RMSE for all system GMM estimators in Tables 5 and 6 are smaller than the bias and MSE in Tables 3 and 4 because the sample size was increased from 50 to 100.

## V. CONCLUSION

We can summarize the main conclusions in the following points:

1. The bias and RMSE of all GMM estimators are increased with increasing by  $\rho$ . While the bias and RMSE of weighted GMM estimators show a much slower increase whenever  $\rho$  increased. Consequently, we conclude that the weighted GMM estimators are more efficiency than the conventional GMM estimators especially when  $\rho \geq 5$ .
2. In case of  $\rho = 0$ , the bias and RMSE values for the conventional level GMM (LEV1, LEV2) estimators equivalent to the bias and RMSE values for the weighted level GMM (WLEV1, WLEV2) estimators. Therefore, not any advantage of use the suggested weighting matrices in this case. While in system GMM estimation, when  $\rho = 0$ , the WCSYS2 estimator performs very well compared with othersystem GMM estimators.
3. In general, the WLEV2 and WJSYS2 estimators perform very well when compared with otherlevel andsystem GMM estimators, respectively, in terms of bias and RMSE for all values of  $\phi$ ,  $T$ , and  $\rho$ . Theoretically, since system GMM estimation use many instruments about level GMM estimation, thus WJSYS2 estimator is more

# International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 10, October 2014

efficient than the WLEV2, which was confirmed by our simulation study. Consequently, we conclude that the WJSYS2 estimation will provide useful parameter estimates for the practitioner.

## REFERENCES

- [1] Abonazel, M. R., "Some Estimation Methods for Dynamic Panel Data Models", PhD Thesis, Institute of Statistical Studies and Research, Cairo University, 2014.
- [2] Ahn, S. C., and Schmidt, P., "Efficient Estimation of Models for Dynamic Panel Data", *Journal of Econometrics*, Vol.68, pp.5-28, 1995.
- [3] Alvarez, J., and Arellano, M., "The Time Series and Cross-Section Asymptotics of Dynamic Panel Data Estimators", *Econometrica*, Vol. 71, pp. 1121-1159, 2003.
- [4] Arellano, M., and Bond, S., "Some Tests of Specification for Panel Data: Monte Carlo Evidence and an Application to Employment Equations", *Review of Economic Studies*, Vol. 58, pp. 277-98, 1991.
- [5] Arellano, M., and Bover, O., "Another Look at the Instrumental Variable Estimation of Error-Components Models", *Journal of Econometrics*, Vol. 68, pp. 29-51, 1995.
- [6] Blundell, R., and Bond, S., "Initial Conditions and Moment Restrictions in Dynamic Panel Data Models", *Journal of Econometrics*, Vol. 87, pp. 115-143, 1998.
- [7] Bun, M., and Kiviet, J., "The Effects of Dynamic Feedbacks on LS and MM Estimator Accuracy in Panel Data Models", *Journal of Econometrics*, Vol. 132, pp. 409-444, 2006.
- [8] Hayakawa, K., "Small Sample Bias Properties of the System GMM Estimator in Dynamic Panel Data Models", *Economics Letters*, Vol. 95, pp. 32-38, 2007.
- [9] Jung, H., and Kwon, H., "An Alternative System GMM Estimation in Dynamic Panel Models", *Hi-Stat Discussion Paper No. 217*, Hitotsubashi University, 2007.
- [10] Newey, W., and Smith, R., "Higher Order Properties of GMM and Generalized Empirical Likelihood Estimators", *Econometrica*, Vol. 72, pp. 219-255, 2004.
- [11] Windmeijer, F., "Efficiency Comparisons for a System GMM Estimator in Dynamic Panel Data Models", In *Innovations in Multivariate Statistical Analysis*, Heijmans, R.D.H., Pollock, D.S.G. and Satorra, A., eds., A Festschrift for Heinz Neudecker, *Advanced Studies in Theoretical and Applied Econometrics*, Vol. 36, Kluwer Academic Publishers, Dordrecht (IFS working paper W98/1), 2000.
- [12] Youssef, A. H., El-sheikh, A. A., and Abonazel, M. R., "Improving the Efficiency of GMM Estimators for Dynamic Panel Models", *Far East Journal of Theoretical Statistics*, Vol. 47, pp. 171-189, 2014.